

VOICE PATCH PANEL

Norden 19" rack mounted Unscreened RJ45 ISDN/Telephone patch panels are available in 1U 25 & 50 port versions to ensure maximum utilization of cabinet space. In addition to this, all panels are supplied with a central & side cable anchor features & dual earthing points. The rear of the panel offers a choice of between 60 to 150 voice pairs to suit PABX & PSTN line connections.

All outlets are numerically identified. Each panel is supplied with wiring label, cable ties and panel mounting accessories, pair manager, earth lead & short form installation instruction.



COMPLIANCE

Class C TIA/EIA 568B.2.1 CAT3 (2 Pair)
EN 50173-1, ISO/IEC 11801:2002

SPECIFICATION

Panel Fitting Type	Rack mountable
Panel Width	483 mm (19")
Panel Height	1U, 44.45 mm Max.
Panel Depth	25 & 50 port 122 mm Nom.
Material	Aluminium
Outlet Style	4 pin RJ45 Unkeyed
IDC	Dual IDC (LSA or 110)
Colour	Black

ORDERING INFORMATION

Part Number	Description
226-25	25 Port Voice Patch Panel
226-50	50 Port Voice Patch Panel

PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
226-25	10 x 1	Carton Box	14.0	15.0	520 x 420 x 305
226-50	10 x 1	Carton Box	17.0	18.0	520 x 420 x 305