

IP DUAL SENSOR THERMAL PTZ CAMERA



ENC-HHP5Z-30X-37

FEATURES

400x300 Uncooled VOx Micro Bolometer Detector

Sensitivity $\leq 40\text{mK}$

25/50/75/100mm Motorized Focus Lens

Areas / Spot / Line Temperature Measurement Rule Support

17 Color Patterns Support

IP67



SPECIFICATION

MODEL	Model No.	ENC-HHP5Z-30X-37
	Type	IP DUAL SENSOR THERMAL PTZ CAMERA
THERMAL CAMERA	Detector Type	Uncooled VOx Focal Plane Arrays
	Effective Pixels	400x300 and Image can be scaled up to 704x576
	Pixel Size	17um
	Thermal Sensitivity (NETD)	$\leq 40\text{ mK}$
	Spectral Range	8~14um
	Image Settings	Brightness, Sharpness, Contrast, 3D DNR, Mirror / Flip, FFC
	Color Palettes	White & Black Hot, Ironbow, Rainbow etc. up to 17 modes
THERMAL LENS	Iris	Auto Fixed IRIS
	Lens	Fixed
	Focus Control	Motorized Focus
	Focal Length	25/50/75/100 mm
	F No	F1.0
	Angle of View	25 mm: 15.4°(H), 11.6° (V) 50mm: 7.7° (H), 5.8° (V) 75 mm: 5.1° (H), 3.8° (V) 100 mm: 3.8° (H), 2.3° (V)
	Detection	25 mm: Human(1.8mx0.5m) - 735 m, Vehicle(4.0mx1.5m) - 2255 m 50 mm: Human(1.8mx0.5m) - 1469 m, Vehicle(4.0mx1.5m) - 4510 m 75 mm: Human(1.8mx0.5m) - 2203 m, Vehicle(4.0mx1.5m) - 6765 m 100 mm: Human(1.8mx0.5m) - 2937 m, Vehicle(4.0mx1.5m) - 9020 m
	Recognition	25 mm: Human(1.8mx0.5m) - 184 m, Vehicle(4.0mx1.5m) - 564 m 50 mm: Human(1.8mx0.5m) - 367 m, Vehicle(4.0mx1.5m) - 1127 m 75 mm: Human(1.8mx0.5m) - 551 m, Vehicle(4.0mx1.5m) - 1691 m 100 mm: Human(1.8mx0.5m) - 734 m, Vehicle(4.0mx1.5m) - 2255 m
	Identification	25 mm: Human(1.8mx0.5m) - 92 m, Vehicle(4.0mx1.5m) - 282 m 50 mm: Human(1.8mx0.5m) - 184 m, Vehicle(4.0mx1.5m) - 564 m 75 mm: Human(1.8mx0.5m) - 275 m, Vehicle(4.0mx1.5m) - 846 m 100 mm: Human(1.8mx0.5m) - 367 m, Vehicle(4.0mx1.5m) - 1127 m
	Fire Detection	25 mm: Fire(0.2mx0.2m) - 147 m, Fire (1.0mx1.0m) - 735 m 50 mm: Fire(0.2mx0.2m) - 294 m, Fire (1.0mx1.0m) - 1471 m 75 mm: Fire(0.2mx0.2m) - 441 m, Fire (1.0mx1.0m) - 2206 m 100 mm: Fire(0.2mx0.2m) - 588 m, Fire (1.0mx1.0m) - 2941 m

★Product specification and availability are subject to change without notice.

►NORDEN® | IP DUAL SENSOR THERMAL PTZ CAMERA - GB. - Version: 3.0

www.nordencommunication.com

IP DUAL SENSOR THERMAL PTZ CAMERA



ENC-HHP5Z-30X-37

MODEL	Model No.	ENC-HHP5Z-30X-37
	Type	IP DUAL SENSOR THERMAL PTZ CAMERA
VISIBLE CAMERA	Image Sensor	1/1.8" Sony CMOS
	Max Resolution	2592x1520
	Focal Length	6.8 ~ 251 mm
	Focus Control	Auto/Semi Auto/Manual
	Angle of View(H)	60.7° ~ 2.3°
	Angle of View(V)	36.8° ~ 1.3°
	Angle of View(D)	70.9° ~ 2.6°
	Max Aperture	F1.5 ~ F4.8
	Optical Zoom	30X
	Digital Zoom	16X
	Electronic Shutter	1s ~ 1/100,000s, Auto/Manual
	Min. illumination	Color:0.001 lux @ F1.5, B/W:0.0001 lux
	AGC	Auto/Manual
	Defog	Smart Defog
S/N Ratio	≥55dB	
WDR	120dB	
VIDEO	Video Compression	Enhanced (H.265, H.264), H.265, H.264, MJPEG
	Frame Rate	Main Stream: Thermal: (704x576) @25/30fps; Visible: (2592x1520, 2304x1296, 1920x1080, 1280x720) @25/30fps Sub Stream: Thermal: (352x288) @25/30fps; Visible: (704x576, 640x480, 352x288) @25/30fps
	Stream Settings	i-Frame, PAL/NTSC, Frame Rate
	Bit Rate Control	CBR, VBR
	Bit Rate	Thermal: 100Kbps ~ 6Mbps Visible: 100Kbps ~ 16Mbps
	BLC	Supported
	HLC	Supported
	OSD	Up to 8 regions
	OSD Type	Title, Week, Date, Time, Text with different colors and adaptable sizes (Small / Medium / Big), Image overlay
	ROI	Up to 8 regions
Privacy Masking	Up to 4 regions	
AUDIO	Audio Compression	G.711A, G.711U, RAW_PCM
	Audio Bitrate	64kbps, 128kbps
	Audio I/O	2/2
SMART	Behaviour Detection	Thermal/Visible: Intrusion (Perimeter), Crossline (Tripwire), Double Crossline (Double Tripwire)
	Intelligent Identification	Thermal/Visible: Loitering Thermal: Region Entry / Exit Detection, Flame Point Detection Visible: Smoke Detection, Flame Detection
	Statistical Analysis	Thermal/Visible: People Counting, Wrong Way Detection, Human and Vehicle Detection, Temperature Detection Visible: Face Detection
	Alarm Management	Motion Detection, Tampering Alarm, Disk Full Alarm, Temperature Alarm, Input / Output Alarm, Network Alarm
	Alarm Notification	E-mail (Notification & Snapshot), HTTP (Alarm icon), FTP (Snapshot & Recording), SD Card (Recording)
TEMPERATURE	Detection Mode	Spot, Line, Area (Total 20 Rules - 1 Full Screen and 19 others)
	Alarm	Over/Difference Alarm
	Accuracy	±2°C / ±2%
	Response Time	≤ 30ms
	Measurement range	-20°C ~ 150°C (-4°F to 302°F)

★Product specification and availability are subject to change without notice.


IP DUAL SENSOR THERMAL PTZ CAMERA



ENC-HHP5Z-30X-37

MODEL	Model No.	ENC-HHP5Z-30X-37
	Type	IP DUAL SENSOR THERMAL PTZ CAMERA
INTERFACE	Protocols	TCP/IP, UDP, IPv4, IPv6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP/RTCP, RTSP, PPPoE, NTP, UPnP, SMTP, IGMP V2/V3, 802.1x, QoS, Unicast, Multicast, SNMP, ARP, SSL / TLS 1.2
	Security	AES 128/256 Encryption, IP Filter, User Authentication (Multiple Privilege Level), HTTPS Authentication, Digest Authentication, User Access Log
	Compatibility	ONVIF (Profile S, G, T, M), CGI/SDK
	Network	1xRJ45 10M/100M Self Adaptive Ethernet Port
	Serial Interface	1xRS485
	BNC	Supported
	Edge Storage	SD Card Slot, Up to 512 GB
	Alarm I/O	9/4
	Heater & Blower	Supported (Optional)
	Max User	32
	Wiper	Supported
	Client Application	EyeGuard
	PAN AND TILT	Pan Range
Pan Speed		Pan Manual Speed: 0.01° ~ 60°/s, Pan Preset Speed: 60°/s
Tilt Range		-75° ~ +40°
Tilt Speed		Tilt Manual Speed: 0.01° ~ 30° /s, Tilt Preset Speed: 30°/s
Preset Accuracy		±0.2°
Number of Presets		400
Power Off Recovery		Supported
3D Position		Supported
PTZ Mode		8 Scan, 6 Track, 12 Patrols (32 Presets per Patrol)
Speed Setup		Auto/Manual (0-8)
GENERAL	Power Supply	36V DC
	Max. Power Consumption	≤100 W
	Working Temperature	-40 °C ~ 70 °C
	Working Humidity	≤95% RH
	Casing	Metal
	Ingress Protection	IP67
	Vandal Resistant	IK10 (Housing)
	Surge Protection	TVS6000V
	Reset Button	Supported
	Dimensions	25/50/75mm Lens: 293 × 420 × 520 mm 100 mm Lens: 333 × 490 × 550 mm
Weight	25/50/75mm Lens: 26 Kg 100mm Len: 28 Kg	

Dimension Unit : mm



★Product specification and availability are subject to change without notice.

IP DUAL SENSOR THERMAL PTZ CAMERA



ENC-HHP5Z-30X-37

ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENC-HHP5Z-30X-37	2MP IP Dual Sensor TemperatureDetection Thermal PTZ Camerawith Visible Lens of 30X Optical Zoom and Thermal Imaging Camera with 400*300 Thermal Resolution and SD Card Slot Support	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENC-HHP5Z-30X-37	Carton Box	-	-