

# DELEGATE MICROPHONE - DIGITAL CONFERENCE SYSTEM



## DESCRIPTION

The NVS-DC900032CM Delegate Unit is a microphone unit designed for meeting participants to speak and listen clearly in a digital conference system. It features a speaking light ring to indicate when the microphone is active, helping maintain smooth and organized communication. Built with an anti-interference design, it effectively resists disruptions from mobile phones, Wi-Fi, Bluetooth, and FM signals, ensuring clear and reliable audio during meetings. The unit integrates seamlessly with the chairman unit and system host, making it ideal for use in professional conference rooms and formal meeting environments.

## FEATURES

- ◉ Equipped with a speaking light ring that indicates active or muted status
- ◉ Chairman unit has priority control, can override delegate units
- ◉ Dual backup design ensures stable and reliable communication
- ◉ Seamless integration into the digital conference system for structured discussions
- ◉ Microphone powers on automatically when speaking
- ◉ 1.23-inch OLED display shows current working status
- ◉ Connection via 8-core aviation T-type cable or standard network cable
- ◉ Powered by system host (passive device – no external power required)

## Specifications

Model	NVS-DC900032CM
Microphone type	Cardioid Condenser Microphone
Microphone neck	Elongated type
Indication	Speech Status
Connection Line	RJ45 and 8 Pin connection
Frequency Response	30Hz – 20kHz

# DELEGATE MICROPHONE - DIGITAL CONFERENCE SYSTEM

Sensitivity	-42dB ± 2dB
Gooseneck Length	430 mm
Optimal Speaking Distance	300 mm
Impedance	2kΩ
Power Consumption	120mA
Weight	0.772 Kg
Base Dimension	167x122x45mm

## FRONT PANEL



## REAR PANEL



# DELEGATE MICROPHONE - DIGITAL CONFERENCE SYSTEM

## ORDERING INFORMATION

Part Number	Description	Standard Quantity
NVS-DC900032CM	DELEGATE MICROPHONE - DIGITAL CONFERENCE SYSTEM	01

## ACCESSORIES INFORMATION

Description	Standard Quantity
2m Conference MIC Cable 8-pin	01
User Manual	01