

IEC C13 PDU WITH C14/INDUSTRIAL 60309 PLUG



NORDEN Power Distribution Units are designed and manufactured in a modularized way exclusively for cabinets. The product is equipped with supply socket modules meeting different systems and standards in the world. The series products can be produced according to customers' special requirements.

COMPLIANCE

EMC & safety:-EN 55022 Class A,EN 55024,EN 61000-3-2, EN 61000-3-3,FCC Part 15 Class A, ICES-003,PSE, VCCI Class A,VDE
 Environmental: RoHS, REACH: Contains No SVHCs
 Socket/Outlet Standard: IEC C13

DESIGN & MATERIALS

Material of Construction	PC/ABS alloy, High Impact flame retardant thermoplastic -UL94-V0
Shell Material & Colour	Aluminium, black
Outlet Qty.	10 way
Plug Type	Industrial Plug / C14 Male Plug
Power Input Style	Left-end single input style
Bracket Installation Style	Frontal Installation Style
Control function	Switch
Commando Plug protection	IP44
Lead length	3m,4m,5m (other cable lengths available on request)

ELECTRICAL & ENVIRONMENTAL DATA

Current Rating	10A, 16A 250VAC
Maximum load current available in	10A or 16A
Input frequency	50 or 60 Hz
Maximum load capacity	4KW
Operating Environment	-5 °C to +45 °C
Operating Relative Humidity	5 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-25°C to +65 °C
Storage Elevation	0-15000 meters

ORDERING INFORMATION

Part Number	Description
17FM-906A06N004X	6 Way PDU, C13 Socket,10Amp, C14 Plug Male,2 Meter Cable Length 19" installation
17FM-910A10N005X	10 Way PDU, C13 Socket,10Amp, C14 Plug Male,4 Meter Cable Length 19" installation
17FM-210A10N005X	10 Way PDU, C13 Socket, 16Amp Industrial IP44 plug Male,4 Meter Cable Length 19" Installation
17FM-916A16N005X	16 Way PDU, C13 Socket,10Amp, C14 Plug Male,4 Meter Cable Length, Vertical Installation