


# 2MP 60FPS LOWLIGHT BULLET CAMERA



## ENC-HBU5M-65R-70

### FEATURES

- 5 ~ 50 mm Motorized Lens
- Smart IR up to 65 m
- ONVIF Profile (S, G, T, M)
- Quad Stream
- Audio and Alarm Support
- PoE, IK10, IP67



### SPECIFICATION

MODEL		ENC-HBU5M-65R-70
CAMERA	Model No.	ENC-HBU5M-65R-70
	Type	2MP 60FPS LOWLIGHT BULLET CAMERA
	Image Sensor	1/2.8" CMOS Progressive 2.0 MegaPixel
	Day / Night	IR Cut Filter with Auto Switch
	Lens Type	Motorized
	Focal Length	5 ~ 50 mm
	Focus	Auto / Manual
	Iris	Fixed Auto Iris
	Angle of View (H)	51.2° ~ 8.7°
	Angle of View (V)	28.0° ~ 4.9°
	Angle of View (D)	58.3° ~ 9.9°
	Angle Adjustment	Bracket; Pan 0~360°, Tilt 0~90°, Rotate 0~360°
	Aperture	F2.0
	Electronic Shutter	1s ~ 1/100,000s, Auto / Manual
	Min. Illumination	Color: 0.001 lux @ F2.0, B/W: 0 lux with IR
	AGC	Auto / Manual
Digital Noise Reduction	2D & 3D DNR, Auto / Manual	
S/N Ratio	≥55 dB	
Defog	Smart Defog	
WDR	120 dB	
Smart IR	Up to 65 m	
Wavelength	850 nm	

★Product specification and availability are subject to change without notice.

# 2MP 60FPS LOWLIGHT BULLET CAMERA



## ENC-HBU5M-65R-70

MODEL	Model No.	ENC-HBU5M-65R-70
	Type	2MP 60FPS LOWLIGHT BULLET CAMERA
DORI	Lens	5 ~ 50 mm
	Detection	88.0 ~ 530.0 m
	Observation	35.2 ~ 212.0 m
	Recognition	17.6 ~ 106.0 m
	Identification	8.8 ~ 53.0 m
VIDEO	Max. Resolution	1920x1080
	Video Compression	Enhanced (H.265,H.264), H.265, H.264, MJPEG
	Frame Rate	Main Stream: (1920x1080, 1280x720, 704x576) @ 50/60fps Sub Stream: (704x576, 640x480, 640x360, 352x288, 320x240) @ 25/30fps Third Stream: (640x480, 352x288, 320x240) @ 25/30fps Fourth Stream: (640x480, 352x288, 320x240) @ 25/30fps (Optional)
	Stream Settings	i-Frame, PAL/NTSC, Frame Rate
	Video Bit Rate	100 kbps ~ 12 Mbps
	Bitrate Type	CBR, VBR
	Image Settings	Brightness, Contrast, Saturation, Sharpness, Day/Night(Color, Mono, Auto), Flip/Mirror/Rotation, Multiple Scene & Profile
	White Balance	Auto, Day/Night, Tungsten, Fluorescent, Shadow, Manual
	Corridor Mode	Supported
	HLC	Supported
	BLC	Supported
	OSD	Up to 8 regions
	OSD Type	Title, Week, Date, Time, Text with different colors and adaptable sizes, Image overlay
	ROI	Up to 8 regions
	Privacy Mask	Up to 4 regions
AUDIO	Audio Compression	G.711 U, G.711A, RAW_PCM
	Audio Bit Rate	64 kbps, 128 kbps
	Audio I/O	1/1
SMART	Behavior Detection	Intrusion (Perimeter), Crossline (Tripwire), Double Crossline (Double Tripwire)
	Intelligent Identification	Loitering, Multi Loitering, Abandoned Object (Object Left), Missing Object (Object Lost)
	Statistical Analysis	Face Detection, People Counting, Human & Vehicle Detection, Abnormal Video & Audio Detection, Wrong Way Detection, Illegal Parking, Tampering / Masking / Scene Change, Abnormal Speed
	Alarm Management	Motion Detection, Tampering (Masking), Input & Output Event, Network Alarm, Disk Alarm, Day Night Switch Alarm, Abnormal Audio Alarm, Pre/Post Alarm Recording, Alarm Recording/Snapshot
	Alarm Notifications	E-mail (Notification and Snapshot), HTTP (Alarm Icon), FTP (Snapshot and Recording), SD Card (Recording)
INTERFACE	Protocols	TCP/IP, UDP, IPv4, IPv6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, IGMP, 802.1X, Unicast, Multicast, QoS, ARP, SNMP, SSL/TLS1.2
	Security	AES 128/256 Encryption, IP Filter, User Authentication (Multiple Privilege Level), 802.1X Authentication (EAP-MD5), HTTPS Authentication, RTSP Authentication, Digest Authentication, User Access Log
	Compatibility	ONVIF Profile (S, G, T, M), SDK / CGI
	Network	1 x RJ45 10M/100M Self Adaptive Ethernet Port
	Alarm I/O	1/1
	Edge Storage	Micro SD Card Slot, up to 512 GB
	ANR	Supported
	Max. User	32
GENERAL	Client Application	EyeGuard
	Power Supply	12V DC, PoE (IEEE 802.3af)
	Max. Power Consumption	≤12 W
	Working Temperature	-40 °C ~ 65 °C
	Working Humidity	≤95% RH
	Ingress Protection	IP67
	Vandal Resistant	IK10
	Surge Protection	TVS4000V
	Reset Button	Supported
	Dimensions	φ110 × 356.33 mm
Net Weight	1.45 Kg	


★Product specification and availability are subject to change without notice.

# 2MP 60FPS LOWLIGHT BULLET CAMERA



## ENC-HBU5M-65R-70

Dimension Unit : mm



### ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENC-HBU5M-65R-70	2MP 60FPS Lowlight IP H.265 Bullet Camera with 5 to 50mm Motorized Lens, PoE, SD Card Slot, WDR, Smart Analytics and 65m IR Support	1
ENB-BCUJ66	Junction Box for Norden Bullet Camera	1
ENB-BCUV67	Pole Mount Bracket for Norden Bullet Camera	1
ENB-BCUH67	Corner Mount Bracket for Norden Bullet Camera	1

### PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENC-HBU5M-65R-70	Carton Box	-	-

★Product specification and availability are subject to change without notice.