

2MP FIXED COMPACT DOME CAMERA



ENV-HCD5F-30R-87

FEATURES

2.8 mm Fixed Lens
Smart IR Up to 30 m
ONVIF Profile (S, G, T)
Built-in Mic
PoE, IP66



SPECIFICATION

MODEL	Model No.	ENV-HCD5F-30R-87
	Type	2MP FIXED COMPACT DOME CAMERA
CAMERA	Image Sensor	1/2.8" CMOS Progressive 2.0 MegaPixel
	Day/Night	Dual IR Cut Filter with Auto Switch
	Lens Type	Fixed
	Focal Length	2.8 mm
	Focus	Fixed
	Iris	Fixed Iris
	Lens Mount	M12
	Angle of View (H)	104.9°
	Angle of View (V)	56.5°
	Angle of View (D)	119.2°
	Angle Adjustment	Pan 0~340°, Tilt 0~75°, Rotate 0~360°
	Aperture	F1.6
	Electronic Shutter	1s ~ 1/100,000s, Auto / Manual
	Min. Illumination	Color: 0.001 lux @ F1.6, B/W: 0 lux with IR
	AGC	Auto / Manual
	Digital Noise Reduction	3D DNR
	S/N Ratio	≥60 dB
Defog	Smart Defog	
WDR	120dB	
Smart IR	Up to 30 m	
IR LEDs	2	
Wavelength	850 nm	

2MP FIXED COMPACT DOME CAMERA



ENV-HCD5F-30R-87


MODEL	Model No.	ENV-HCD5F-30R-87
	Type	2MP FIXED COMPACT DOME CAMERA
DORI	Lens	2.8 mm
	Detection	38.6 m
	Observation	15.3 m
	Recognition	7.7 m
	Identification	3.8 m
VIDEO	Max. Resolution	1920x1080
	Video Compression	Enhanced (H.265, H264), H.265, H.264
	Frame Rate	Main Stream: (1920×1080, 1280×720, 704×480, 640×480) @ 30fps; (1920×1080, 1280×720, 704×576, 640×480) @ 25fps Sub Stream: (704×480, 704×240, 640×360, 352×240) @ 30fps; (704×576, 704×288, 640×360, 352×288) @ 25fps
	Stream Settings	I-Frame, PAL/NTSC, Frame Rate (1~30FPS), SVC
	Video Bit Rate	32 kbps ~ 6 Mbps
	Bitrate Type	CBR, VBR
	Image Settings	Brightness, Contrast, Saturation, Sharpness, Rotation/Mirror, Gain, Exposure, Day/Night
	White Balance	Auto, Semi Auto, Sunshine, Daylight, Warm Light, Filament, Nature Light, Lock WB, Manual
	HLC	Supported
	BLC	Supported
	OSD	Up to 1 Regions
	OSD Type	Title, Week, Date, Time, Text with different colors and adaptable sizes (16×16, 32×32, 48×48)
	ROI	Up to 8 regions
	Privacy Mask	Up to 4 regions
AUDIO	Audio Compression	G.711A, G.711U, ADPCM_D
	Audio Bit Rate	8 kbps, 32 kbps, 48 kbps
	Audio I/O	N/A
	Built-in Mic	Supported with noise cancellation
SMART	Behavior Detection	Intrusion (Perimeter), Crossline (Tripwire)
	Intelligent Identification	N/A
	Statistical Analysis	N/A
	Alarm Management	Motion Detection, Tampering (Masking), IP Address Conflict, Disk Alarm (Full & R/W Error)
INTERFACE	Protocols	TCP/IP, UDP, IPv4, ICMP, HTTP, HTTPS, DHCP, DNS, DDNS, RTSP, FTP, NTP, UPnP, P2P, QoS, Unicast
	Security	AES 128 Video Encryption, IP Filter, User Authentication (Multiple Privilege Level)
	Compatibility	ONVIF Profile (S, G, T), SDK/API/CGI
	Network	1 x RJ45 10M/100M Self Adaptive Ethernet Port
	Alarm I/O	N/A
	Edge Storage	Micro SD Card Slot, Up to 512 GB
	ANR	Supported
	Cable Interface	Pig Tail
	Remote Connection	≤2
	Max. Users	32
Web Language	15	
Client Application	EyeConnect	
GENERAL	Power Supply	PoE (802.3af)
	Max. Power Consumption	≤7 W (PoE)
	Working Temperature	-40 °C ~ 65 °C
	Working Humidity	≤95% RH (non-condensing)
	Ingress Protection	IP66
	Surge Protection	TVS4000V
	Reset Button	Supported
	Dimensions	Φ117×96 mm
Net Weight	0.29 kg	

2MP FIXED COMPACT DOME CAMERA



ENV-HCD5F-30R-87

Dimension Unit : mm



ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENV-HCD5F-30R-87	2MP IR IP H.265 Compact Dome Camera with 2.8mm Fixed Lens, PoE, SD Card Slot, WDR, Built-in Mic and 30m IR Support	1
ENB-BTEW65	Wall Mount for NordenLite Series Turret Camera	1
ENB-BTEJ67	Junction Box for Norden Fixed Lens Turret Camera	1
ENB-BTDV66	Pole Mount Bracket for Norden Turret Camera	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENV-HCD5F-30R-87	Carton Box	0.42	140x140x120