

2MP FIXED MINI DOME CAMERA



ENC-HCV5F-15R-63

FEATURES

2.8 mm (Optional 4 mm) Fixed Lens

Smart IR up to 15 m

ONVIF Profile (S, G, T, M)

Triple Stream

Built-in Mic

PoE, IP67



SPECIFICATION

MODEL	Model No.	ENC-HCV5F-15R-63
	Type	2MP FIXED MINI DOME CAMERA
CAMERA	Image Sensor	1/2.8" CMOS Progressive 2.0 MegaPixel
	Day/Night	IR Cut Filter with Auto Switch
	Lens Type	Fixed
	Focal Length	2.8 mm (Optional 4 mm)
	Digital Zoom	16x
	Focus	Fixed
	Iris Type	Fixed Iris
	Angle of View (H)	101.5° (Optional 80.3°)
	Angle of View (V)	50.5° (Optional 41.0°)
	Angle of View (D)	113.0° (Optional 90.1°)
	Angle Adjustment	Pan ± 45°, Tilt 0~72°, Rotate 0~360°
	Aperture	F1.6
	Electronic Shutter	1s ~ 1/100,000s, Auto / Manual
	Min. Illumination	Color: 0.001 lux @ F1.6, B/W: 0 lux with IR on
	AGC	Auto / Manual
Digital Noise Reduction	2D & 3D DNR, Auto / Manual	
S/N Ratio	≥55 dB	
Defog	Smart Defog	
WDR	120 dB	
Smart IR	Up to 15 m	
Wavelength	850 nm	

★Product specification and availability are subject to change without notice.

2MP FIXED MINI DOME CAMERA



ENC-HCV5F-15R-63

MODEL	Model No.	ENC-HCV5F-15R-63
	Type	2MP FIXED MINI DOME CAMERA
DORI	Lens	2.8 mm (Optional 4.0 mm)
	Detection	44.0 m (Optional 56.5 m)
	Observation	17.6 m (Optional 22.6 m)
	Recognition	8.8 m (Optional 11.3 m)
	Identification	4.4 m (Optional 5.6 m)
VIDEO	Max. Resolution	1920x1080
	Video Compression	Enhanced(H.265,H.264), H.265, H.264, MJPEG
	Frame Rate	Main Stream: (1920x1080, 1280x720) @ 25/30fps Sub Stream: (704x576, 640x480, 640x360, 352x288, 320x240) @ 25/30fps Third Stream: (640x480, 352x288, 320x240) @ 25/30fps
	Stream Settings	i-Frame, PAL/NTSC, Frame Rate
	Video Bit Rate	100 kbps ~ 12 Mbps
	Bitrate Type	CBR, VBR
	Image Settings	Brightness, Contrast, Saturation, Sharpness, Day/Night, Flip/Mirror/Rotation, Multiple Scene & Profile
	White Balance	Auto, Day/Night, Tungsten, Fluorescent, Shadow, Manual
	Corridor Mode	Supported
	HLC	Supported
	BLC	Supported
	OSD	Up to 8 regions
	OSD Type	Title, Week, Date, Time, Text with different colors and adaptable sizes, Image overlay
	ROI	Up to 8 regions
	Privacy Mask	Up to 4 regions
AUDIO	Audio Compression	G.711A, G.711U, RAW_PCM
	Audio Bit Rate	64 kbps, 128 kbps
	Audio I/O	1/1
	Built-in Mic	Supported
SMART	Behavior Detection	Intrusion (Perimeter), Crossline (Tripwire), Double Crossline (Double Tripwire)
	Intelligent Identification	Loitering, Multi Loitering, Abandoned Object (Object Left), Missing Object (Object Lost)
	Statistical Analysis	Face Detection, People Counting, Human & Vehicle Detection, Abnormal Video & Audio Detection, Wrong Way Detection, Illegal Parking, Tampering / Masking / Scene Change, Abnormal Speed
	Alarm Management	Motion Detection, Tampering, Input & Output Event, Network Alarm, Disk Alarm, Day Night Switch Alarm, Pre/Post Alarm Recording, Alarm Recording/Snapshot
INTERFACE	Alarm Notifications	E-mail(Notification & Snapshot), HTTP(Alarm icon), FTP(Snapshot & Recording), SD Card(Recording)
	Protocols	TCP/IP, UDP, IPv4, IPv6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, IGMP, 802.1X, Unicast, Multicast, QoS, ARP, SNMP, SSL/TLS1.2
	Security	AES 128/256 Video Encryption, IP Filter, User Authentication (Multiple Privilege Level), 802.1X Authentication, HTTPS Authentication, RTSP Authentication, Digest Authentication, User Access Log
	Compatibility	ONVIF Profile (S, G, T, M), SDK/CGI
	Network	1 x RJ45 10M/100M Self Adaptive Ethernet Port
	Edge Storage	Micro SD Card Slot, up to 512 GB
	ANR	Supported
	Remote Connection	≤10
	Max.User	32
	Web Language	15
Client Application	EyeGuard	

★Product specification and availability are subject to change without notice.


2MP FIXED MINI DOME CAMERA



ENC-HCV5F-15R-63

MODEL		ENC-HCV5F-15R-63
Type		2MP FIXED MINI DOME CAMERA
GENERAL	Power Supply	12V DC, PoE (IEEE 802.3af)
	Max. Power Consumption	≤5 W
	Working Temperature	-40 °C ~ 65°C
	Working Humidity	≤95% RH (non-condensing)
	Casing	Metal
	Ingress Protection	IP67
	Vandal Resistant	IK10
	Surge Protection	TVS4000V
	Reset Button	Supported
	Dimensions	99.6 × 99.6 × 63.3 mm
Net Weight	0.48 Kg	

Dimension Unit : mm



ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENC-HCV5F-15R-63 (With 2.8 mm Lens)	2MP IR IP H.265 Vandal Proof Compact Dome Camera with 2.8mm Fixed Lens, WDR, PoE, SD Card Slot, Built-in Mic Smart Analytics and 15m IR Support	1
ENC-HCV5F-15R-63 (With 4 mm Lens)	2MP IR IP H.265 Vandal Proof Compact Dome Camera with 4 mm Fixed Lens, WDR, PoE, SD Card Slot, Built-in Mic Smart Analytics and 15m IR Support	1
ENB-BCDJ65	Junction Box for Norden Dome Camera	1
ENB-BCDQ65	Pendent Cap for Norden Dome Camera	1
ENB-BCDP66	Pendent Mount for Norden Dome Camera	1
ENB-BCDW66	Wall Mount Bracket for Norden Dome Camera	1
ENB-BCDV66	Pole Mount Bracket for Norden Dome Camera	1
ENB-BCPH65	Corner Mount Bracket for Dome Camera	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENC-HCV5F-15R-63	Carton Box	-	-

★Product specification and availability are subject to change without notice.