


ADSS MULTI-LOOSE TUBE FIBRE OPTIC CABLE

These cables are constructed with FRP Central Strength Member, Waterproof tape over the tube to give water and moisture resistance, Aramid yarn strength member for better tensile strength and rodent protection, and a PE outer jacket which gives an excellent tensile strength, mechanical, rodent, ultraviolet, and environmental protection. They come in larger delivery lengths, so can be used in long-distance communication systems, building interconnections, trunklines, LAN, and distribution networks.





COMPLIANCE

ITU-T G652.B OS1
 ITU-T G652.D/G655/G657.A1/G657.A2 OS2
 ITU-T G651.1 OM1 OM2 OM3 OM4
 IEC60793-2-10 type A1a.1/A1b OM1/OM2
 IEC60793-2-10 type A1a.2 OM3
 IEC60793-2-10 type A1a.3 OM4
 ISO/IEC 11801 , ISO/IEC 24702
 ANSI/TIA/EIA 568.3-D
 ROHS compliant Directive 2002/95/EC
 LSZH: IEC 60332-1, IEC 60754, IEC 61034

MECHANICAL & ENVIRONMENTAL CHARACTERISTICS

Characteristics	Short Term
Max. Tensile Load	3000N
Max. Crush Load	3000N/10cm
Operating Temp.	-10°C to +70°C
Sheath Material	Standard: PE, Optional: LSZH, PVC or Other

ORDERING INFORMATION

Part Number	Fibre Count	No. of Loose Tube	Outer Diameter (mm)	Cable Weight (kg/km)	Dynamic	
					Short (mm)	Long (mm)
4019-340240S2CL	24	6	11.0	110.0	20D	10D

ORDERING GUIDE

Cable Type	Jacket	Fibre/Tube	Fibre Count	Fibre Type (FXX)	Jacket Colour (CL)
4019	1=PVC 2=LSZH 3=PE	1=12 F/T 2=08 F/T 3=06 F/T 4=04 F/T	No. of Fibre	OM1=62.5/125 OM1 OM2=50/125 OM2 OM3=50/125 OM3 OM4=50/125 OM4 OS1=9/125 [G652.B] OS1 OS2=9/125 [G652.D] OS2 500=9/125 [G655] OS2 7A1=9/125 [G657.A1] OS2 7A2=9/125 [G657.A2] OS2	As noted

CL: BK(Black), OR(Orange), YL(Yellow), GN(Green), AQ(Aqua), RD(Red), BL(Blue)

ADSS MULTI-LOOSE TUBE FIBRE OPTIC CABLE

PACKING INFORMATION

Part Number	Packing Length	Packing Mode	N.W (kg)	G.W (kg)
4019-340240S2CL	2000 x 1	Wooden Drum	220.0	250.0