

2MP FIXED BULLET CAMERA



ENC-HCB5F-30R-69

FEATURES

- 2.8 mm Fixed Lens
- Smart IR up to 30 m
- ONVIF Profile (S, G, T, M)
- Quad Stream
- Audio and Alarm Support
- PoE, IP67



SPECIFICATION

MODEL		Model No.	ENC-HCB5F-30R-69
CAMERA		Type	2MP FIXED BULLET CAMERA
		Image Sensor	1/2.8" CMOS Progressive 2.0 MegaPixel
		Day/Night	IR Cut Filter with Auto Switch
		Lens Type	Fixed
		Focal Length	2.8 mm
		Digital Zoom	16x
		Focus	Auto / Manual
		Iris Type	Fixed Iris
		Lens Mount	Φ14
		Angle of View (H)	101.5°
		Angle of View (V)	50.5°
		Angle of View (D)	116.0°
		Angle Adjustment	Bracket; Pan 0~360°, Tilt 0~90°, Rotate 0~360°
		Aperture	F2.0
Electronic Shutter	1s ~ 1/100,000s, Auto / Manual		
Min. Illumination	Color: 0.001 lux @ F2.0, B/W: 0 lux with IR		
AGC	Auto / Manual		
Digital Noise Reduction	2D & 3D DNR, Auto / Manual		
S/N Ratio	≥55 dB		
Defog	Smart Defog		
WDR	120 dB		
Smart IR	Up to 30 m		
Wavelength	850 nm		

★Product specification and availability are subject to change without notice.

2MP FIXED BULLET CAMERA



ENC-HCB5F-30R-69

MODEL	Model No.	ENC-HCB5F-30R-69
	Type	2MP FIXED BULLET CAMERA
DORI	Lens	2.8 mm
	Detection	44.0 m
	Observation	17.6 m
	Recognition	8.8 m
	Identification	4.4 m
VIDEO	Max. Resolution	1920x1080
	Video Compression	Enhanced (H.265, H.264), H.265, H.264, MJPEG
	Frame Rate	Main Stream: (1920x1080, 1280x720) @ 25/30fps Sub Stream: (704x576, 640x480, 640x360, 352x288, 320x240) @ 25/30fps Third Stream: (640x480, 352x288, 320x240) @ 25/30fps Fourth Stream: (640x480, 352x288, 320x240) @ 25/30fps (Optional)
	Stream Settings	i-Frame, PAL/NTSC, Frame Rate
	Video Bit Rate	100 kbps ~ 12 Mbps
	Bitrate Type	CBR, VBR
	Image Settings	Brightness, Contrast, Saturation, Sharpness, Day/Night, Flip/Mirror/Rotation, Multiple Scene & Profile
	White Balance	Auto, Day/Night, Tungsten, Fluorescent, Shadow, Manual
	Corridor Mode	Supported
	HLC	Supported
	BLC	Supported
	OSD	Up to 8 regions
	OSD Type	Title, Week, Date, Time, Text with different colors and adaptable sizes, Image overlay
	ROI	Up to 8 regions
	Privacy Mask	Up to 4 regions
AUDIO	Audio Compression	G.711A, G.711U, RAW_PCM
	Audio Bit Rate	64 kbps , 128 kbps
	Audio I/O	1/1
SMART	Behavior Detection	Intrusion (Perimeter), Crossline (Tripwire), Double Crossline (Double Tripwire)
	Intelligent Identification	Loitering, Multi Loitering, Abandoned Object (Object Left), Missing Object (Object Lost)
	Statistical Analysis	Face Detection (Capture), People Counting, Human & Vehicle Classification, Abnormal Video & Audio Detection, Wrong Way Detection, Illegal Parking, Signal Bad, Abnormal Speed
	Alarm Management	Motion Detection, Tampering (Masking), Input & Output Event, Network Alarm, Disk Alarm, Day Night Switch Alarm, Abnormal Audio Alarm, Pre/Post Alarm Recording, Alarm Recording/Snapshot
	Alarm Notification	E-mail (Notification and Snapshot), HTTP (Alarm Icon), FTP (Snapshot and Recording), SD Card (Recording)
INTERFACE	Protocols	TCP/IP, UDP, IPv4, IPv6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP , IGMP, 802.1X, Unicast, Multicast, QoS, ARP, SNMP, SSL/TLS1.2, RTMP (Optional)
	Security	AES 128/256 Encryption, IP Filter, User Authentication (Multiple Privilege Level), 802.1X Authentication (EAP-MD5), HTTPS Authentication, RTSP Authentication, Digest Authentication, User Access Log
	Compatibility	ONVIF Profile (S, G, T, M), SDK/CGI
	Network	1 x RJ45 10M/100M Self Adaptive Ethernet Port
	Alarm I/O	1/1
	Edge Storage	Micro SD Card Slot, up to 512 GB
	ANR	Supported
	Max. User	32
GENERAL	Client Application	EyeGuard
	Power Supply	12V DC , PoE (IEEE 802.3af)
	Max. Power Consumption	≤6.5 W
	Working Temperature	-40°C ~ 65°C
	Working Humidity	≤95% RH (non-condensing)
	Ingress Protection	IP67
	Surge Protection	TVS4000V
	Reset Button	Supported
	Dimensions	187.6 × 64 × 64mm
Net Weight	0.6 kg	


★Product specification and availability are subject to change without notice.

2MP FIXED BULLET CAMERA



ENC-HCB5F-30R-69

Dimension Unit : mm



ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENC-HCB5F-30R-69	2MP IR IP H.265 Compact Bullet camera with 2.8mm Fixed lens, PoE, SD card slot, WDR, Smart Analytic, and 30m IR support	1
ENB-BCUJ67	Junction Box for Norden Bullet Camera	1
ENB-BCUV67	Pole Mount Bracket for Norden Bullet Camera	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENC-HCB5F-30R-69	Carton Box	-	-