

GLOBAL SHUTTER CAMERA



ENC-HBUAF-00R-72

FEATURES

Global Shutter Technology
25mm (Optional 16/35mm) Fixed Lens
AI & Radar Trigger
IP66, IK10



SPECIFICATION

MODEL	Model No.	ENC-HBUAF-00R-72
	Type	GLOBAL SHUTTER CAMERA
CAMERA	Image Sensor	1/1.1" Sony Pregius-S 8.0 Megapixel
	Day / Night	IR Cut Filter with Auto Switch
	Focal Length	25mm (Optional 16 / 35 mm) Fixed Lens
	Lens Type	Fixed
	Lens Mount	C Mount
	Aperture	F1.8
	Shutter	Global Shutter
VIDEO	Min. Illumination	B/W: 0 lux
	Max. Resolution	3840x2160
	Video Compression	H.264, MJPEG
	Frame Rate	3840x2160 @ 20 fps
INTERFACE	Compatibility	ONVIF
	Network	RJ45 Ethernet Port
	Serial Interface	RS 485
	Trigger I/O	RS 485
GENERAL	Working Temperature	-10 °C ~ 60 °C
	Working Humidity	≤90% RH
	Ingress Protection	IP66
	Vandal Resistant	IK10 (Housing)

ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENC-HBUAF-00R-72	8MP IP Global Shutter Bullet Camera with 25mm (Optional 16 / 35mm) Fixed Lens, AI and WDR Support	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENC-HBUAF-00R-72	Carton Box	-	-

★Product specification and availability are subject to change without notice.