

12MP MOTORIZED LOWLIGHT BULLET CAMERA



ENC-HBUCM-60R-69

FEATURES

3.6 ~ 12.8 mm Motorized Lens

Smart IR up to 60 m

ONVIF Profile (S, G, T, M)

Triple Stream

Built-in Mic & Speaker

PoE, IP67



SPECIFICATION

MODEL	Model No.	ENC-HBUCM-60R-69
	Type	12MP MOTORIZED LOWLIGHT BULLET CAMERA
CAMERA	Image Sensor	1/1.7" CMOS Progressive 12.0 MegaPixel
	Day / Night	IR Cut Filter with Auto Switch
	Lens Type	Motorized
	Focus	Auto / Manual
	Iris Type	P-Iris (Auto/Manual)
	Focal Length	3.6 ~ 12.8 mm
	Angle of View (H)	93.8° ~ 34.0°
	Angle of View (V)	70.1° ~ 25.8°
	Angle of View (D)	117.1° ~ 42.6°
	Angle Adjustment	Bracket; Pan 0~360°, Tilt 0~90°, Rotate 0~360°
	Aperture	F1.5 ~ F3.3
	Electronic Shutter	1s ~ 1/100,000s, Auto / Manual
	Min. Illumination	Color: 0.001 lux @ F1.5, B/W: 0 lux with IR
	AGC	Auto / Manual
	Digital Noise Reduction	2D & 3D DNR
S/N Ratio	≥55 dB	
Defog	Smart Defog	
WDR	120 dB	
Smart IR	Up to 60 m	
Wavelength	850 nm	

★Product specification and availability are subject to change without notice.

12MP MOTORIZED LOWLIGHT BULLET CAMERA



ENC-HBUCM-60R-69


MODEL	Model No.	ENC-HBUCM-60R-69
	Type	12MP MOTORIZED LOWLIGHT BULLET CAMERA
DORI	Lens	3.6 ~ 12.8 mm
	Detection	134.2 ~ 392.3 m
	Observation	53.6 ~ 158.0 m
	Recognition	26.0 ~ 78.0 m
	Identification	12.0 ~ 38.8 m
VIDEO	Max. Resolution	4000x3000
	Video Compression	Enhanced (H.265, H.264), H.265, H.264, MJPEG
	Frame Rate	Main Stream: (4000x3000, 2592x1944, 1280x960) @ 25/30fps Sub Stream: (704x576, 640x480, 352x288) @ 25/30fps Third Stream: (640x480, 352x288, 320x240) @ 25/30fps
	Stream Settings	i-Frame, PAL/NTSC, Frame Rate
	Video Bit Rate	100 kbps ~ 16 Mbps
	Bitrate Type	CBR, VBR
	Image Settings	Brightness, Contrast, Saturation, Sharpness, Day/Night (Color, Mono, Auto), Flip/Mirror/Rotation, Multiple Scene & Profile
	White Balance	Auto, Day/Night, Tungsten, Fluorescent, Shadow, Manual
	Corridor Mode	Supported
	HLC	Supported
	BLC	Supported
	OSD	Up to 8 regions
	OSD Type	Title, Week, Date, Time, Text with different colors and adaptable sizes, Image overlay
	ROI	Up to 8 regions
	Privacy Mask	Up to 4 regions
AUDIO	Audio Compression	G.711 U, G.711A, , RAW_PCM
	Audio Bit Rate	64 kbps, 128 kbps
	Audio I/O	1/1
	Built-in Mic	Supported
	Built-in Speaker	Supported
SMART	Behavior Detection	Intrusion (Perimeter), Crossline (Tripwire), Double Crossline (Double Tripwire)
	Intelligent Identification	Loitering, Multi Loitering, Abandoned Object (Object Left), Missing Object (Object Lost)
	Statistical Analysis	Face Detection, People Counting, Human & Vehicle Detection, Abnormal Video & Audio Detection, Wrong Way Detection, Tampering / Masking / Scene Change, Abnormal Speed
	Alarm Management	Motion Detection, Tampering (Masking), Input & Output Event, Network Alarm, Disk Alarm, Day Night Switch Alarm, Abnormal Audio Alarm, Pre/Post Alarm Recording, Alarm Recording/Snapshot
	Alarm Notifications	E-mail (Notification and Snapshot), HTTP (Alarm Icon), FTP (Snapshot and Recording), SD Card (Recording)
INTERFACE	Protocols	TCP/IP, UDP, IPv4, IPv6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, IGMP, 802.1X, Multicast, SNMP
	Security	AES 128/256 Encryption, IP Filter, User Authentication (Multiple Privilege Level), 802.1X Authentication (EAP-MD5), HTTPS Authentication, RTSP Authentication, Digest Authentication, User Access Log
	Compatibility	ONVIF Profile (S, G, T, M), SDK / CGI
	Network	1 x RJ45 10M/100M Self Adaptive Ethernet Port
	Alarm Interface	1/1
	Serial Interface	1 x RS485
	Edge Storage	Micro SD Card Slot, up to 1TB
	ANR	Supported
	Max. User	32
	Client Application	EyeGuard
GENERAL	Power Supply	12V DC , PoE (IEEE 802.3af)
	Max. Power Consumption	≤13.2 W
	Working Temperature	-40 °C ~ 65 °C
	Working Humidity	≤95% RH
	Ingress Protection	IP67
	Vandal Resistant	IK10
	Surge Protection	TVS4000V
	Reset Button	Supported
Dimensions	Ø110x365.3 mm	
Net Weight	1.5 kg	

12MP MOTORIZED LOWLIGHT BULLET CAMERA



ENC-HBUKM-60R-69

Dimension Unit : mm



ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENC-HBUKM-60R-69	12MP Lowlight IR IP H.265 Bullet camera with 3.6 to 12.8mm Motorized Lens, P-Iris, PoE, SD card slot, WDR, Smart Analytics, Built-in Mic, Built in Speaker and 60M IR support	1
ENB-BCUJ66	Junction Box for Norden Bullet Camera	1
ENB-BCUV67	Pole Mount Bracket for Norden Bullet Camera	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENC-HBUKM-60R-69	Carton Box	-	-