

## WALL MOUNT EXTERNAL CABINET IP66



Norden Wall Mount Cabinet IP66 designed for external telecommunication purpose. The smart design and professional engineering provide easy installation and maintenance. It is complied with ANSI/EIARS-310-D, EC 297-2, DIN 41491, PART 1, DIN 41497, PART 7, GB/T3047.2-92, ETSI standards.

### FEATURES

- Single section front metal door with an opening angle of 130 degrees.
- IP66 rating ensures dustproof and waterproof protection.
- The wall-mount cabinet features two cable entry holes at the bottom.
- Includes a filter, louvers, and a cam lock for security and ventilation.
- The default body color is RAL 7035 (Light Grey), with customization options available.

Material	GI (Galvanized Iron)
Material Thickness	Mounting L-Angle : 2.0 mm Main Body : 1.5 mm Canopy : 1.5 mm Top Cover : 1.5 mm Bottom Cover : 1.5 mm
Surface Finish	7 Tank Process (Degrease, Acid pickling, Rust prevention & Pure water cleaning, etc)
Degree of Protection	IP66
Door Opening Angle	130 Degree
No. of Cable Entry	2
Cable Entry Position	Bottom
Max. Load Capacity	100Kgs
Color	RAL 7035 (Light Grey) or customizable

### ORDERING INFORMATION

Part Number	Description	Capacity (U)	Dimension(mm)
20FY-096020R2	09U 600W X 440D IP66 Wall Mount External Cabinet, RAL 7035	09	600 X 440 X 501

### DEFAULT ACCESSORIES

Pole Mounting Brackets & Accessories	1 Set
Mounting Hardware	Pack of 10
Part Number	Description
1335-P001X	1U Plastic Cable Management with 5 rings