

WHITE LIGHT STROBE ILLUMINATOR



ENI-ISA010-100W

FEATURES

42 pcs LED
Flash Support
100 m Intelligent Strobe Support
IP66



SPECIFICATION

MODEL	Model No.	ENI-ISA010-100W
	Type	WHITE LIGHT STROBE ILLUMINATOR
GENERAL	Beam Angle	10°
	Beam Distance	Intelligent Strobe 100 m
	Best Distance for LPR	50 ~ 100 m
	Flash Trigger Method	One Port Flash Trigger Input
	Synchronization Port	One Port Strobe Trigger Input
	Response Time	≤20μs
	Design Lifetime	≥50000 Hrs
	Color	White
	LED	42 pcs LED
	Wavelength	455 nm
	Power Supply	220V AC
	Power Consumption	≤85W (Strobe), ≤200W (Flash)
	Working Temperature	-40 °C ~ 70 °C
	Working Humidity	≤90%
	Ingress Protection	IP66
Surge Protection	Common Mode: 6KV, Differential Mode: 3KV	
Material	Aluminium Die-casting Housing	
Panel	Tempered Glass	
Dimensions	281 x 260 x 117 mm	
Net Weight	4.7 kg	
INSTALLATION	Power	The Power and LED Panel Wires must be Oriented Downward to Prevent Water Intrusion.
	Earthing	Lighting Safety Precautions must be Taken and Power Wires must be Grounded.
	Settings	Gently Modify the Bolt of Brightness, Sensor and Time.
	Installation	Professional Electricians or Quality Technicians Should Install and Adjust.
	Caution	Do Not Open the Case and Remove the Power Supply.

