

4MP VISIBLE CAMERA MODULE



ENC-HPT7Z-30X-39-MOD

FEATURES

5.3 ~ 159 mm Motorized Lens

ONVIF Profile (S, G, T, M)

Triple stream

Audio and Alarm Support



SPECIFICATION

MODEL	Model No.	ENC-HPT7Z-30X-39-MOD
	Type	4MP VISIBLE CAMERA MODULE
CAMERA	Image Sensor	1/2.8 Sony CMOS
	Day / Night	IR Cut Filter with Auto Switch
	Lens Type	Motorized
	Focal Length	5.3 ~ 159 mm
	Focus Control	Auto/Semi-Auto/Manual
	Iris Type	Fixed Iris
	Angle of View (H)	56.3° ~ 2.7°
	Angle of View (V)	33.3° ~ 1.5°
	Angle of View (D)	65.4° ~ 3.0°
	Optical Zoom	30x
	Digital Zoom	16x
	Aperture	F1.6 ~ F4.3
	Electronic Shutter	1s ~ 1/100,000s, Auto / Manual
	Min. Illumination	Color: 0.01 Lux @ F1.6, B/W: 0.001 Lux with IR
AGC	Auto / Manual	
Digital Noise Reduction	2D & 3D DNR, Auto / Manual	
S/N Ratio	≥55 dB	
Defog	Smart Defog	
WDR	120 dB	

4MP VISIBLE CAMERA MODULE



ENC-HPT7Z-30X-39-MOD

MODEL	Model No.	ENC-HPT7Z-30X-39-MOD
	Type	4MP VISIBLE CAMERA MODULE
DORI	Lens	5.3 ~ 159 mm
	Detection	104 ~ 3120 m
	Observation	41.6 ~ 1248 m
	Recognition	20.8 ~ 624 m
	Identification	10.4 ~ 312 m
VIDEO	Max. Resolution	2592 x 1520
	Video Compression	Enhanced (H.265, H.264), H.265, H.264, MJPEG
	Frame Rate	Main Stream: (2592×1520, 2560×1440, 2304×1296, 1920×1080, 1280×720) @25/30fps Sub Stream: (704×576, 640×480, 352×288) @25/30fps Third Stream: (640×480, 352×288, 320×240) @25/30fps
	Stream Settings	i-Frame, PAL/NTSC, Frame Rate
	Video Bit Rate	100 kbps ~ 12 Mbps
	Bitrate Type	CBR, VBR
	Image Settings	Brightness, Contrast, Saturation, Sharpness, Day/Night, Flip/Mirror/Rotation, Multiple Scene & Profile
	White Balance	Auto, Day/Night, Tungsten, Fluorescent, Shadow, Manual
	HLC	Supported
	BLC	Supported
	OSD	Up to 8 regions
	OSD Type	Title, Week, Date, Time, Text with different colors and adaptable sizes, Image overlay
	ROI	Up to 8 regions
	Privacy Mask	Up to 4 regions
AUDIO	Audio Compression	G.711 U, G.711A, RAW_PCM
	Audio Bit Rate	64 kbps, 128 kbps
	Audio I/O	1/1
SMART	Behavior Detection	Intrusion (Perimeter), Crossline (Tripwire), Double Crossline (Double Tripwire)
	Intelligent Identification	Loitering, Smoke Detection, Flame Detection
	Statistical Analysis	Face Detection, People Counting, Human and Vehicle Detection, Wrong Way Detection, Illegal Parking.
	Alarm Management	Motion Detection, Tampering (Masking), Input & Output Event, Network Alarm, Disk Alarm, Day Night Switch Alarm, Abnormal Audio Alarm, Pre/Post Alarm Recording, Alarm Recording/Snapshot
	Alarm Notifications	E-mail (Notification and Snapshot), HTTP (Alarm Icon), FTP (Snapshot and Recording), SD Card (Recording)
INTERFACE	Protocols	TCP/IP, UDP, IPv4, IPv6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, IGMP, 802.1X, Unicast, Multicast, QoS, ARP, SNMP, SSL/TLS1.2
	Security	AES 128/256 Encryption, IP Filter, User Authentication (Multiple Privilege Level), 802.1X Authentication (EAP-MD5), HTTPS Authentication, RTSP Authentication, Digest Authentication, User Access Log
	Compatibility	ONVIF Profile (S, G, T, M), SDK / CGI
	Network	1 x RJ45 10M/100M Self Adaptive Ethernet Port
	Alarm I/O	1/1
	Edge Storage	Micro SD Card Slot, up to 512 GB
	ANR	Supported
	Max. User	32
	Client Application	EyeGuard
GENERAL	Power Supply	12V DC, PoE (IEEE 802.3af)
	Max. Power Consumption	≤7 W
	Working Temperature	-20°C ~ 60°C
	Dimensions	112.7 × 47.9 × 55.7 mm
	Net Weight	0.28 Kg


★Product specification and availability are subject to change without notice.

4MP VISIBLE CAMERA MODULE



ENC-HPT7Z-30X-39-MOD

Dimension Unit : mm



ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENC-HPT7Z-30X-39-MOD	4MP Visible Camera Module with 30x Optical Zoom, SD Card Slot, and Smart Analytics	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENC-HPT7Z-30X-39-MOD	Carton Box	-	-