

8MP MOTORIZED VANDAL DOME CAMERA



ENC-HVDAM-50R-67

FEATURES

3.6 ~ 11 mm Motorized Lens

Smart IR up to 50 m


ONVIF Profile (S, G, T, M)

Triple Stream

Audio and Alarm Support

FIPS 140-3 Level 3 Compliant

PoE, IK10, IP67



SPECIFICATION

MODEL	Model No.	ENC-HVDAM-50R-67
	Type	8MP MOTORIZED VANDAL DOME CAMERA
CAMERA	Image Sensor	1/1.8" CMOS Progressive 8.0 MegaPixel
	Day/Night	IR Cut Filter with Auto Switch
	Lens Type	Motorized
	Focal Length	3.6 ~ 11 mm
	Focus	Auto / Manual
	Iris Type	P-Iris
	Angle of View (H)	109° ~ 47.5°
	Angle of View (V)	57.5° ~ 26.6°
	Angle of View (D)	123.9° ~ 54.4°
	Angle Adjustment	Pan 0~355°, Tilt 0~75°, Rotate 0~355°
	Aperture	F1.3
	Electronic Shutter	1s ~ 1/100,000s, Auto / Manual
	Min. Illumination	Color: 0.001 lux @ F1.3, B/W: 0.0008 lux @ F1.3, 0 lux with IR on
	AGC	Auto / Manual
	Digital Noise Reduction	2D & 3D DNR, Auto / Manual
	S/N Ratio	≥55 dB
Defog	Smart Defog	
WDR	120 dB	
Smart IR	Up to 50 m	
Wavelength	850 nm	

★Product specification and availability are subject to change without notice.

8MP MOTORIZED VANDAL DOME CAMERA



ENC-HVDAM-50R-67

MODEL	Model No.	ENC-HVDAM-50R-67
	Type	8MP MOTORIZED VANDAL DOME CAMERA
DORI	Lens	3.6 ~ 11 mm
	Detection	84.0 ~ 185.0 m
	Observation	33.6 ~ 74.0 m
	Recognition	16.8 ~ 37.0 m
	Identification	8.4 ~ 18.5 m
VIDEO	Max. Resolution	3840x2160
	Video Compression	Enhanced (H.265, H.264), H.265, H.264, MJPEG
	Frame Rate	Main Stream: (3840x2160, 2592x1944, 2592x1520, 2560x1440, 2304x1296, 1920x1080, 1280x720) @ 25/30fps Sub Stream: (704x576, 640x480, 352x288) @ 25/30fps Third Stream: (640x480, 352x288, 320x240) @ 25/30fps
	Stream Settings	i-Frame, PAL/NTSC, Frame Rate
	Video Bit Rate	100 kbps ~ 16 Mbps
	Bitrate Type	CBR, VBR
	Image Settings	Brightness, Contrast, Saturation, Sharpness, Day/Night (Color, Mono, Auto), Flip/Mirror/Rotation, Multiple Scene & Profile
	White Balance	Auto, Day/Night, Tungsten, Fluorescent, Shadow, Manual
	Corridor Mode	Supported
	HLC	Supported
	BLC	Supported
	OSD	Up to 8 regions
	OSD Type	Title, Week, Date, Time, Text with different colors and adaptable sizes, Image overlay
	ROI	Up to 8 regions
	Privacy Mask	Up to 4 regions
	AUDIO	Audio Compression
Audio Bit Rate		64 kbps , 128 kbps
Audio I/O		1/1
SMART	Behavior Detection	Intrusion (Perimeter), Crossline (Tripwire), Double Crossline (Double Tripwire)
	Intelligent Identification	Loitering, Multi Loitering, Abandoned Object (Object Left), Missing Object (Object Lost)
	Statistical Analysis	Face Detection (Capture), People Counting, Human & Vehicle Classification, Abnormal Video & Audio Detection, Wrong Way Detection, Illegal Parking, Signal Bad, Abnormal Speed
	Alarm Management	Motion Detection, Tampering (Masking), Input & Output Event, Network Alarm, Disk Alarm, Day Night Switch Alarm, Abnormal Audio Alarm, Pre/Post Alarm Recording, Alarm Recording/Snapshot
INTERFACE	Alarm Notifications	E-mail (Notification & Snapshot), HTTP (Alarm icon), FTP (Snapshot & Recording), SD Card (Recording)
	Protocols	TCP/IP, UDP, IPv4, IPv6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP/RTSP/RTCP, PPPoE, NTP, UPnP, SMTP, IGMP, SRTP, 802.1X, QoS, Unicast, Multicast, ARP, SNMP, TLS/SSL
	Security	AES 128/256 Video Encryption, IP Filter, User Authentication (Multiple Privilege Level), Prevent Brute-Force Attack, Secure Boot, Signed Firmware, 802.1X Authentication (EAP-TLS), HTTPS Authentication, RTSP Authentication, Digest Authentication, User Access Log , AES 128/256 SD Card Encryption, WSS
	Compatibility	ONVIF Profile (S, G, T, M), SDK/CGI
	Network	1 x RJ45 10M/100M Self Adaptive Ethernet Port
	Alarm I/O	2/1
	Edge Storage	Micro SD Card Slot, up to 1TB
	ANR	Supported
	Cable Interface	Pig Tail
	Max User	32
Remote Connection	≤10	
Web Language	15	
Client Application	EyeGuard	

★Product specification and availability are subject to change without notice.


8MP MOTORIZED VANDAL DOME CAMERA



ENC-HVDAM-50R-67

MODEL		ENC-HVDAM-50R-67
Type		8MP MOTORIZED VANDAL DOME CAMERA
GENERAL	Power Supply	12V DC , PoE (IEEE 802.3af)
	Max, Power Consumption	≤8.8 W
	Working Temperature	-40 °C ~ 65 °C
	Working Humidity	≤95% RH (non-condensing)
	Casing	Metal
	Ingress Protection	IP67
	Vandal Resistant	IK10
	Surge Protection	TVS4000V
	Reset Button	Supported
	Dimensions	Φ130x113.3 mm
Net Weight	0.8 Kg	

Dimension Unit : mm



ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENC-HVDAM-50R-67	8MP H.265 IR IP Vandal Proof Dome Camera with 3.6 to 11mm Motorized Lens, WDR, PoE, SD Card Slot, Smart Analytics and 50m IR Support	1
ENB-BCDJ67	Junction Box for Norden Dome Camera	1
ENB-BCDQ66	Pendent Cap for Norden Dome Camera	1
ENB-BCDP66	Pendant Mount for Norden Dome Camera	1
ENB-BCDW66	Wall Mount for Norden Dome Camera	1
ENB-BCDV66	Pole Mount for Norden Dome Camera	1
ENB-BCPH65	Corner Mount Bracket for Norden Dome Camera	1

PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENC-HVDAM-50R-67	Carton Box	-	-

★Product specification and availability are subject to change without notice.