

# 4MP MOTORIZED LPR BULLET CAMERA



## ENC-HBU7M-80R-75

### FEATURES

8 ~ 32 mm Motorized Lens

Smart IR up to 80 m

ONVIF Profile (S, G, T, M)

Triple Stream

Built-in Mic and Speaker

PoE, IP67, IK10



### SPECIFICATION

MODEL	Model No.	ENC-HBU7M-80R-75
	Type	4MP MOTORIZED LPR BULLET CAMERA
CAMERA	Image Sensor	1/1.8" CMOS Progressive 4.0 MegaPixel
	Day / Night	IR Cut Filter with Auto Switch
	Lens Type	Motorized
	Focus	Auto / Manual
	Iris Type	Auto Iris
	Focal Length	8 ~ 32 mm
	Angle of View (H)	41.1° ~ 14.0°
	Angle of View (V)	23.0° ~ 7.9°
	Angle of View (D)	47.0° ~ 16.8°
	Angle Adjustment	Bracket; Pan 0~360°, Tilt 0~90°, Rotate 0~360°
	Aperture	F1.6
	Electronic Shutter	1s ~ 1/100,000s, Auto / Manual
	Min. Illumination	Color: 0.001 lux @ F1.6, B/W: 0.0008 lux @ F1.6, 0 lux with IR on
	AGC	Auto / Manual
	Digital Noise Reduction	2D & 3D DNR
	S/N Ratio	≥55 dB
Defog	Smart Defog	
WDR	120 dB	
Smart IR	Up to 80 m	
Wavelength	850 nm	

★Product specification and availability are subject to change without notice.

►NORDEN® | 4MP MOTORIZED LPR BULLET CAMERA - GB. - Version: 3.0

www.nordencommunication.com

# 4MP MOTORIZED LPR BULLET CAMERA



## ENC-HBU7M-80R-75

MODEL	Model No.	ENC-HBU7M-80R-75
	Type	4MP MOTORIZED LPR BULLET CAMERA
VIDEO	Max. Resolution	2688x1520
	Video Compression	Enhanced (H.265, H.264), H.265, H.264, MJPEG
	Frame Rate	Main Stream: (2688x1520, 2560x1440, 2304x1296, 1920x1080, 1280x720) @ 50/60fps Sub Stream: (704x576, 640x480, 352x288) @ 50/60fps Third Stream: (640x480, 352x288, 320x240) @ 50/60fps
	Stream Settings	i-Frame, PAL/NTSC, Frame Rate
	EIS	Supported
	Video Bit Rate	100 kbps ~ 16 Mbps
	Bitrate Type	CBR, VBR
	Image Settings	Brightness, Contrast, Saturation, Sharpness, Day/Night (Color, Mono, Auto), Flip/Mirror/Rotation, Multiple Scene & Profile
	White Balance	Auto, Day/Night, Tungsten, Fluorescent, Shadow, Manual
	Corridor Mode	Supported
	HLC	Supported
	BLC	Supported
	OSD	Up to 8 regions
	OSD Type	Title, Week, Date, Time, Text with different colors and adaptable sizes, Image overlay
ROI	Up to 8 regions	
Privacy Mask	Up to 4 regions	
AUDIO	Audio Compression	G.711 U, G.711A, RAW_PCM
	Audio Bit Rate	64 kbps, 128 kbps
	Audio I/O	1/1
	Built-in Mic	Supported
	Built-in Speaker	Supported
SMART	Max. Vehicle Speed	120 km/h
	Identification	Vehicle Type & Color, License Plate Recognition
	White / Black List	Supported (up to 20000 records in the camera)
	Smart Search	LPR Smart Search
INTERFACE	Protocols	TCP/IP, UDP, IPv4, IPv6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, IGMP, SRTP, 802.1X, Multicast, Unicast, SNMP
	Security	AES 128/256 Video Encryption, IP Filter, User Authentication (Multiple Privilege Level), Prevent Brute-Force Attack, Signed Firmware, 802.1X Authentication (EAP-TLS), HTTPS Authentication, RTSP Authentication, Digest Authentication, User Access Log, AES 128/256 SD Card Encryption, WSS
	Compatibility	ONVIF Profile (S, G, T, M), SDK / CGI
	Network	1 x RJ45 10M/100M Self Adaptive Ethernet Port
	Alarm Interface	1 / 2
	Serial Interface	1 x RS485
	Edge Storage	Micro SD Card Slot, up to 1TB
	ANR	Supported
	Cable Interface	Pig Tail
	Remote Connection	≤10
	Max. User	32
	Web Language	15
	Client Application	EyeGuard
	GENERAL	Power Supply
Max. Power Consumption		≤13.2 W
Working Temperature		-40 °C ~ 65 °C
Working Humidity		≤95% RH
Ingress Protection		IP67
Vandal Resistant		IK10
Surge Protection		TVS4000V
Reset Button		Supported
Dimensions		Φ110x356.3 mm
Net Weight		1.7 kg


★Product specification and availability are subject to change without notice.

# 4MP MOTORIZED LPR BULLET CAMERA



ENC-HBU7M-80R-75

Dimension Unit : mm



## ORDERING INFORMATION

Part Number	Description	Standard Quantity
ENC-HBU7M-80R-75	4MP 60FPS Lowlight IR IP H.265 LPR Bullet Camera with 8 ~ 32mm Motorized Lens PoE, SD Card Slot, WDR, Smart Analytics and 80m IR Support	1
ENB-BCUJ66	Junction Box for Norden Bullet Camera	1
ENB-BCUV67	Pole Mount Bracket for Norden Bullet	1

## PACKING INFORMATION

Part Number	Packing Mode	Gross weight(Kg)	Dimension(mm)
ENC-HBU7M-80R-75	Carton Box	-	-