

FLOOR STANDING EXTERNAL CABINET - IP55



Norden floor standing cabinet IP55 designed for external telecommunication purpose. The smart design and professional engineering provides easy installation and maintenance. It is comply with GB/T 19183, IEC 61969, ANSI/EIA RS-310-D, IEC 297- 2, DIN 41491, PART 1, DIN 41497, PART 7, GB/T3047.2-92,1 GB/T3047.2-92, ETSI standards.

FEATURES

- Intelligent design ensures easy installation.
- 19" External Cabinet-Dual wall type, Ip55
- The cabinet has a double-wall construction. It is made up of the main body, roof, rear panel, side panel, and base. It also has a front toughened glass door with black waterproof rubber seal.
- The double wall type rear panel, the dual side panel, the bolts are fixed inside.

- The cabinet can adopt 19-inch structure to install, it can install the mounting panel or according to the custom design and has natural wind cooling.
- The cabinet can be placed with fans on the top cover and a hole punched in the bottom of two sides with a dust-proof cover. The air conditioner is available as an option.
- Protection Rank: IP55 EN 60529/10.91
- Bottom wire path, cover with rubber
- The front door has a handle lock.

Material	Galvanized Sheet
Deg. of Protection	IP 55
Surface finish	Degrease, acid pickling, rust prevention and parkerizing, pure water cleaning, static electricity plastic painting
Loading Capacity	1000 Kg
Material thickness	Mounting Profile: 2.0 mm, Other: 1.5-2.0 mm

Top fan & door knob



Rail & Bottom



Handle lock



FLOOR STANDING EXTERNAL CABINET - IP55

No.	Item	600 wide	800 wide	Materials	Treatment	Note
1.	Frame	2	2	2.0mm Galvanized Sheet	Powder coating	
2.	Front Door	1	1	1.5mm Galvanized Sheet	Powder coating	Without file box
3.	Side Door	2	2	1.5mm Galvanized Sheet	Powder coating	Unremovable
4.	Back Door	1	1	1.5mm Galvanized Sheet	Powder coating	
5.	Lock	1	1	\	\	Handle Lock
6.	Top Cover	1	1	1.5mm Galvanized Sheet	Powder coating	With water proof panel
7.	Fans	1	1	1.2mm Galvanized Sheet	Powder coating	
8.	AC Fan	2 or 4	2 or 4	\	\	D>800,4 pcs
9.	Door Seal	1	1	Black Rubber	\	
10.	Door Knob	1	1	Galvanized Sheet T=1.5	GE	
11.	Fixed Shelf	2	2	Galvanized Sheet T=1.5	Powder coating	Color customized
12.	Fan power cord	1	1	\	\	L=1.5 to 2.0M
13.	Bottom panel	1	1	Galvanized Sheet T=1.5	Powder coating	
14.	Mounting profile	4	4	Galvanized Sheet T=2.0	Zinc plated	
15.	Modular Finger type vertical cable manager		2	ABS+Galvanized Sheet	Powder coating	Available only with 800mm depth cabinet
16.	Blanking panel		2	ABS+Galvanized Sheet	Powder coating	

ORDERING INFORMATION

Part Number	Description	Capacity (U)	Dimension (mm)
1326-426812X	42U 600 x 800 IP55 Front Glass/Back Metal Door Cabinet	42	600 x 800 x 2055
1326-426112X	42U 600 x 1000 IP55 Front Glass/Back Metal Door Cabinet	42	600 x 1000 x 2055
1326-428812X-V1	42U 800 x 800 IP55 Front Glass/Back Metal Door Cabinet with Modular Finger type vertical cable management including vertical blanking panel	42	800 x 800 x 2070
1326-428812X-V2	42U 800 x 800 IP55 Front Glass/Back Metal Door Cabinet with Thermostat & Modular Finger type vertical cable management including vertical blanking panel	42	800 x 800 x 2070

X: R1(RAL 9004), R2(RAL 7035), R3(RAL 9010)

PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
1326-426812X	1 x 1	Carton Box	200	220	600 x 800 x 2070
1326-426112X	1 x 1	Carton Box	220	240	600 x 1000 x 2070
1326-428812X-V1	1 x 1	Carton+Wooden Pallet	210	230	870 x 870 x 2150