

FLOOR STANDING EXTERNAL CABINET - IP65



The Norden range of floor standing cabinet IP65 designed for external telecommunication purpose. The smart design and professional engineering provides easy installation and maintenance. It is comply with ANSI/EIA RS-310-D, IEC 297-2, DIN 41491 PART 1, DIN 41497 PART 7, GB/T3047.2-92, ETSI standards.

FEATURES

- IP 65 Ingress protection based on ISO/IEC 60529
- 19" profile for mounting the panels.
- Front and rear operations
- Plinth/base with a height of 400mm with front access (800x375mm)
- Removable cable entry plate with 9 x PG26 IP65 cable glands
- Removable maintenance plate to ensure base frame access.
- Gasket between base and cabinet for maximum IP 65 protection
- Slope roof construction, equipped with eyebolt for lifting purpose.
- Cylindrical side cable management with patch cable deposits 5 nos each
- 3-point locking mechanism with pad lock option on swing handle

Material	Zinc plated panel
Deg. of Protection	IP 65
Surface finish	Powder Coated
Loading capacity	300-500 Kg
Material thickness	Mounting Profile: 2.0 mm, Wall & Door: 1.5 mm

ORDERING INFORMATION

Part Number	Description	Capacity (U)	Dimension (mm)
1328-129E22X	12U 900 x 500 IP 65 Front & Back Metal Door Floor Standing Cabinet	12	900 x 500 x 700
1328-186622X	18U 600 x 600 IP 65 Front & Back Metal Door Floor Standing Cabinet	18	600 x 600 x 988
1328-188122X	18U 800 x 1000 IP 65 Front & Back Metal Door Floor Standing Cabinet	18	800 x 1000 x 988

X: R1(RAL 9004), R2(RAL 7035), R3(RAL 9010)

PACKING INFORMATION

Part Number	Packing Qty.	Packing Mode	N.W (kg)	G.W (kg)	Dimension (mm)
1328-129E22X	1 x 1	Carton Box	90	100	980 x 580 x 730
1328-186622X	1 x 1	Carton Box	110	120	680 x 680 x 1068
1328-188122X	1 x 1	Carton Box	130	140	880 x 1080 x 1068